

Desktopdisplays

EA241F



Ideal for multi-screen usage with a narrow bezel and sleek look, the EA241F maximises productivity with best in class ergonomics.

- In-demand display size – the popular 23.8" display with Full HD resolution is the perfect size for busy office workspaces.
- Best in form and function – future-ready design with 3-sided ultra-narrow bezel, available in black or white, complementing a fresh professional office interior.
- Energy efficiency – reduce your energy consumption by up to 30% by enabling the built-in Human and Ambient Light Sensors ensuring the display is only powered up according to usage conditions.
- Maximum attention to health and well-being – the ergonomic height adjustment from 0 to 150 mm; built-in Low Blue Light and Flicker-Free technology; plus integrated ambient light sensor all combines to
- Ease of multi-display control – manage the settings of up to 5 displays in a multi-monitor configuration via the master display with ControlSync® technology.

Specificaties

| | |
|--|---|
| Panel Technologie | IPS TFT with W-LED backlight |
| Aspect Ratio | 16:9 |
| Helderheid (cd/m ²) | 250 |
| Contrast Ratio | 1000:1 |
| Pixel Pitch (mm H/V) | 0,275 |
| Response Time (typ.) [ms] | 5 |
| Screen Tilt [°] | -5 - 25 |
| Height adjustable stand [mm] | 150 |
| Screen Swivel [°] | 170 - -170 |
| Screen Rotate [°] | 0 - 90 |
| [AVSpecificationPortraitDimensionsWidthMm] | 319 |
| [AVSpecificationPortraitDimensionsHeightMm] | 615 |
| [AVSpecificationPortraitDimensionsDepthMm] | 250 |
| [AVSpecificationLandscapeDimensionsWidthMm] | 319 |
| [AVSpecificationLandscapeDimensionsHeightMm] | 615 |
| [AVSpecificationLandscapeDimensionsDepthMm] | 250 |
| Energy Efficiency | Energy efficiency class: C, Human sensor, Ambient light sensor, Energy consumption: 11 kWh/1000 h |
| Ecological Standards | Energy Star 8.0, Voldoet aan ErP, Voldoet aan RoHS, TCO 9.0, WEEE |
| Beelddiagonaal (inches / cm) | 24 |
| Colours [Mio.] | 16 |
| Colour Gamuts | 72% NTSC, 101.6 % sRGB, 75.3% AdobeRGB |
| Frame Material | Aluminum alloy (front); metal (back) |
| Horizontal Frequency [kHz] | 31.5 - 83 |
| Vertical Frequency [Hz] | 50 - 75 |
| Operating Humidity (min) [%] | 20 |
| Operating Humidity (max) [%] | 80 |
| Bevestiging (VESA/Aantal Punten/Pitch mm) | 100 x 100 |

| | |
|------------------------------------|--|
| Colour Versions | Zwarte voorkant, Zwarte achterkant, Witte voorkant, Witte achterkant |
| Cable Management | True |
| Plug & Play | VESA DDC2Bi, DDC2B/2Bi, VESA DDC/CI |
| Audio | Geïntegreerde speakers (1W + 1W) |
| Adjust Functions | Geavanceerde NTAA (Non-Touch-Auto-Adjustment) |
| Safety & Ergonomics | ISO 9241-307 (pixel failure class I), Low Blue Light, PSB, RoHS, TÜV Ergonomics, UL/C-UL or CSA, TCO 8.0, WEEE, CE, EAC, EnergyStar 8.0, ErP, Flicker-free |
| Beperkte fabrieksgarantie (jaren.) | 3 jaar garantie incl. achtergrondverlichting, Optioneel 1e tot 3e jaar 24/7 gebruiksgarantie, Optionele verlenging van de garantie van 4 tot 5 jaar |
| Storage Temperature [°C] | -10 - 60 |
| Storage Humidity [%] | 10 |
| Storage Humidity [%] | 85 |
| [AVSpecificationPowerSavingModeW] | < 2 (Networked Standby) |
| Accessoires | |
| Shipping Content | Stroomkabel, Installatiehandleiding, DisplayPoort-kabel, USB-kabel, Control Sync-kabel, Monitor |
| Digital | DisplayPort, HDMI, USB ver. 3.1 (2 down / 1 up), DVI-D |
| Analog | D-sub 15 pin |
| Power Supply | 100-240 V, Internal Power Supply, 0.9 A/0.5 A |
| Grootte Omlijsting (L/R) mm | 1 |
| Grootte Omlijsting (L) mm | 15 |
| Optimum Resolution | 1920 x 1080 at 60 Hz |

