

NEC M260XS

ORDER CODE: 60003074

NEC M260XS Professional Short-Throw Projector

Get great performance while saving the environment. Advanced Eco features help to substantially lower your operating cost without compromising on quality and flexibility. Less shadow and glare gives the presenter more space to engage with his audience and enhances the experience with interactive white boards.

The M260XS is particularly suited for classrooms and small to medium sized meeting rooms.



DELIVERING GENUINE BENEFITS

Get Great Performance while not compromising on quality and ease of use.

Save the Environment with latest Eco technology by minimizing your power consumption and consumables replacements.

Large Flexibility in positioning the projector and minimized cost for replacements.

Intuitive Use of latest Eco and projection technology due to user-centric design.

Peace of Mind with future-proof connectivity.

Wide Format allows you to enjoy extra space in presentations and other office files.

Less Shadow and Glare - not standing in the light beam gives you more space to engage with your audience when presenting.



OUTSTANDING PERFORMANCE

- **Short-Throw Projection** with 0.47:1 throw ratio
- **Minimized Cost of Ownership** due to long lamp life and filter cleaning intervals
- **Innovative ECO Functions** to reduce power consumption
- **Great Connectivity** due to numerous analog and digital connection terminals as well as network capability
- **Intuitive and Easy Operation** with user centric design



SPECIAL CHARACTERISTICS

Auto Power ON/OFF; Automaattinen Eco-tila; Automatic and manual Keystone Correction ($V = \pm 20^\circ$); Carbon Savings Meter; Colour Management; Content Transmission via Network; DICOM Simulation; Direct Power-Off Function; High Altitude Mode; Kensington-turvallukko; Keypad Lock; Magnify; Off-Timer; Optional User Logo; OSD with 27 languages; Password Security System; Quick On/Off; Remote control and administration via LAN and RS232; Security Bar; USB-katselulaite JPEG:lle; Valinnainen WLAN; Virtual Remote for direct PC control; Wall Colour Correction



ECO Innovation: Auto ECO Mode; Green one touch ECO and AV mute button; 75% AV mute function

Energy Efficiency: ECO scheduler; Intelligent Power Management; Longer lamp life; Reduced power consumption. Only 0,4W stand-by; Software scheduling

Ecological Materials: 100% recyclable packaging; Downloadable manuals; ECO packaging

Ecological Standards: RoHS compliant; ErP compliant

Technical Specification NEC M260XS

IMAGE	
Display	3 x 1,6 cm (0,63") p-Si LCD Panel with MLA
Native Resolution	1024 x 768 (XGA)
Aspect Ratio	4:3
Brightness ¹	2600 ANSI Lumen (approx. 80% in Eco Mode)
Contrast Ratio ¹	2000:1
Lamp	185 W AC (145 W AC Eco Mode)
Lamp Life [hrs]	5000 (6000 Eco Mode)
Lens	F= 2,0, f= 00 mm
Projection Factor	0,47 : 1
Projection Angle [°]	37,3 - 38,6
Projection Distance [m]	0,6 – 1,1
Screen Size (diagonal) [cm]	Minimum: 152,4 / 60"; Maximum: 279,4 / 110"
Zoom	Digital Zoom
Focus Adjustment	Manual
Supported Resolutions	1360 x 768 (WXGA); 1366 x 768 (WXGA); 1600 x 900 (WXGA++); 1440 x 900 (WXGA+); 1680 x 1050 (WSXGA+); 1152 x 870 (MAC 21"); 1400 x 1050 (SXGA+); 1280 x 960 (SXGA); 1280 x 800 (WXGA); 1280 x 768 (WXGA); 1280 x 720 (HDTV 720p); 1280 x 1024 (SXGA); 1280 x 1024 (MAC 23"); 640 x 480 (VGA/MAC 13"); 1600 x 1200 (UXGA); 1920 x 1080 (HDTV 1080i/60; HDTV 1080i/50); 1152 x 864 (XGA); 1024 x 768 (XGA); 800 x 600 (SVGA); 832 x 624 (MAC 16"); 720 x 576 SDTV 480p/480i; 720 x 480 SDTV 576p/576i
Frequency	Horizontal: 15–100 kHz (RGB: 24 kHz– 100 kHz); Vertical: 50 – 120 Hz
CONNECTIVITY	
RGB (analog)	Input: 2 x Mini D-sub 15-pin, compatible to component (YPbPr)
Video	Input: 1 x RCA
HDMI®	Input: 1 x HDMI® (Deep Color, Lip sync)
S-Video	Input: 1 x Mini DIN 4-pin
Audio	Input: 2 x 3.5 mm Stereo Mini Jack; Input: 2 x RCA Stereo; Output: 1 x 3.5 mm Stereo Mini Jack (variable)
PC Control	Input: 1 x D-Sub 9 pin (RS-232) (male)
LAN	1 x RJ45
USB	2 x Type A (USB 2.0 high speed); 1 x Type B
Video Signals	PAL; PAL60; NTSC; SECAM; NTSC 4.43; PAL-M
REMOTE CONTROL	
Remote Control	Source Select; Auto Adjust; Aspect Ratio; Automatic Picture Adjustment; Picture Adjust; Audio Control; Picture Mode; Jäädytys; Apu-Eco-mode; Digitaalinen zoom; Esitys- ja hiiriohjaus; AV-mykistys; ID-asetus
ELECTRICAL	
Power Supply	100-240 V AC; 50 - 60 Hz
Power Consumption [W]	239 (Normal) / 193 (Eco) / 8 (Network Stand-by) / 0,4 (Stand-by)
MECHANICAL	
Dimensions (W x H x D) [mm]	398 x 140 x 309,5 (without lens and feet)
Weight [kg]	4,0
Fan Noise [dB (A)]	29 / 35 (Eco / Normal)
ENVIRONMENTAL CONDITIONS	
Operating Temperature [°C]	5 to 40
Operating Humidity [%]	20 to 80
Storage Temperature [°C]	-10 to 50
Storage Humidity [%]	20 to 80
OPTIONAL ACCESSORIES	
Optional Accessories	Lamp (NP15LP); Langaton LAN-moduuli (NP02LM2); Seinäasennussarja (NP02WK)
ERGONOMICS	
Safety and Ergonomics	CE; TÜV GS; RoHS; Gost-R
Speakers [W]	1 x 10 (mono)
WARRANTY	
Projectors	3 years pan-European service
Lamp	6 months, max. 1000 hrs
SHIPPING CONTENT	
Shipping Contents	IR Remote Control (RD-448E); Mini D-SUB Signal Cable; Power Cord (1,8 m); Security Sticker; Users Manual on CD-ROM; Quick Setup Guide; Lens Cap

¹Compliance with ISO21118-2005