

Desktopdisplays

Sharp/ NEC MultiSync EA271U



NEC MultiSync

- Nieuwste connectiviteitsstandaard USB-C - optimale connectiviteit: vervang video-, audio-, stroom- en USB-kabels door slechts één enkele kabel om uw laptop/tablet met de monitor te verbinden.
- Maximale aandacht voor de gezondheid en het welzijn van de gebruiker - met uitstekende ergonomische hoogteverstelling tussen 0 en 150 mm; ingebouwde Low Blue Light- en Flicker-Free-technologie; plus g
- Uitstekende vorm en functionaliteit - toekomstgericht ontwerp met 3-zijdige, dunne behuizing, leverbaar in zwart of wit voor een even fris als professioneel ogend kantoorinterieur.
- Automatische aanpassing van het stroomverbruik - om onnodig stroomverbruik te minimaliseren, passen de aanwezigheidssensor en omgevingslichtsensoren de helderheid van het scherm aan op basis van de aa
- Het gemak van meerdere schermen - met de ControlSync®-technologie beheer je de instellingen van maximaal 8 schermen in een configuratie met meerdere monitoren via het hoofdscherm.

Specificaties

Panel Technologie	IPS TFT with W-LED backlight
Aspect Ratio	16:9
Helderheid (cd/m2)	350
Contrast Ratio	1300:1
[AVSpecificationDynamicContrastRatio]	9000:1
Kleuren Display	1064.64
Reactietijd (grijs naar grijs gem) ms	5
Pixel Pitch (mm H/V)	0,155
Viewing Angle [°]	178
Special Characteristics	Omgevingslichtsensor voor geoptimaliseerde helderheidsniveaus, ControlSync®, Aanpasbare instellingen, DDC/CI compatible, Eco-modi, Frame Comp, ErgoDesign®, Height adjustable stand (150 mm) with 90° Pivot features, Aanwezigheidssensor, LED-achtergrondverlichtingstechnologie, Picture-by-Picture, Voet met snelontgrendelingsmechanisme en handgreep, Versatile and easy installation (VESA standard) with NaViSet and NaViKey
Energy Efficiency	Ambient light sensor, Carbon Footprint Meter / Carbon Savings Meter, ECOMode, Energy consumption: 22 kWh/1000 h, Energy efficiency class: F, Human sensor, LED backlight technology
Ecological Standards	Minimaal gebruik van schadelijk materiaal
Ecological Materials	Energy Star 8.0, Voldoet aan ErP, Voldoet aan RoHS, TCO 8.0
Werkende Temperatuur (oC)	5 - 35
Storage Temperature [°C]	-10 - 60
Storage Humidity [%]	10
Storage Humidity [%]	85
Beelddiagonaal (inches / cm)	27
Beelddiagonaal (inches / cm)	68
Colour Gamuts	110 % sRGB, 81.6% AdobeRGB, 78% NTSC
Digital	DisplayPort, USB Type C (60 W), HDMI, USB ver. 3.1 (3 down / 1 up)
Horizontal Frequency [kHz]	31.5 - 135
Vertical Frequency [Hz]	30 - 75
Grootte Omlijsting (L/R) mm	1
Grootte Omlijsting (U) mm	1

Colour Versions	Zwarte voorkant, Zwarte achterkant, Witte voorkant, Witte achterkant
Cable Management	True
Plug & Play	EDID Standard, VESA DDC2Bi, VESA DDCi
Audio	1W + 1W (uitschakelbaar), Koptelefoonaansluiting
Adjust Functions	DV-modus, Eco-modus, Aanwezigheidssensor, Intelligent stroombeheer, sRGB
Safety & Ergonomics	CE, EAC, ErP, Flicker-free, ISO 9241-307 (pixel failure class I), Low Blue Light, PSB, RoHS, TÜV Ergonomics, TÜV GS, UL/C-UL or CSA
Beperkte fabrieksgarantie (jaren.)	3 jaar garantie incl. achtergrondverlichting, Optioneel 1e tot 3e jaar 24/7 gebruiksgarantie, Optionele verlenging van de garantie van 4 tot 5 jaar
Height adjustable stand [mm]	150
Screen Rotate [°]	-90 - 90
[AVSpecificationPortraitDimensionsWidthMm]	362
[AVSpecificationPortraitDimensionsDepthMm]	250
[AVSpecificationLandscapeDimensionsWidthMm]	612
[AVSpecificationLandscapeDimensionsDepthMm]	250
[AVSpecificationPortraitDimensionsHeightMinMm]	629
[AVSpecificationPortraitDimensionsHeightMaxMm]	652
[AVSpecificationLandscapeDimensionsHeightMinMm]	378
[AVSpecificationLandscapeDimensionsHeightMaxMm]	528
Optimum Resolution	3840 x 2160 at 60 Hz
Supported Resolution	1024 x 768, 1280 x 1024, 1152 x 864, 1600 x 1200, 1920 x 1080, 1920 x 1440, 2560 x 1440, 640 x 480, 800 x 600, 832 x 624, 3840 x 2160
Accessoires	Control Sync-kabel, Weergave, DisplayPoort-kabel, Stroomkabel, Installatiehandleiding, USB-kabel
Shipping Content	Control Sync-kabel, Weergave, DisplayPoort-kabel, Stroomkabel, Installatiehandleiding, USB-kabel
Stroomverbruik aan-modus (IEC62087:2012)	150 (max.), 30 (Eco Mode 1), 38 (Eco Mode 2), 38 (shipping)
Power Supply	1.6 A/0.75 A, 100-240 V, Integrated Power Supply
Bevestiging (VESA/Aantal Punten/Pitch mm)	100 x 100
Kensington-slot	True
Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80
Gewicht met standaard (kg)	10



Design and specifications are subject to change without prior notice. All information was correct at time of print. Microsoft, Excel, PowerPoint, OneDrive, SharePoint, Active Directory, Windows Server, and Windows are either registered trademarks or trademarks of Microsoft Corporation in the US and/or other countries. Adobe and PostScript 3 are either registered trademarks or trademarks of Adobe Systems Incorporated in the US and/or other countries. Google Drive, Gmail, Android, and Google Cloud Print are trademarks of Google LLC. The Google Drive trademark is used with permission from Google LLC. Box is a trademark, service mark, or registered trademark of Box, Inc. QR Code is a registered trademark of DENSO WAVE INCORPORATED in Japan and other countries. AirPrint and Mac are trademarks of Apple Inc., registered in the US and other countries. PCL is a registered trademark of Hewlett_x0002_Packard Company. Qualcomm DirectOffice is a product of Qualcomm Technologies, Inc. and/or its subsidiaries. Qualcomm is a trademark of Qualcomm Incorporated, registered in the US and other countries. DirectOffice is a trademark of CSR Imaging US, LP, registered in the US and other countries. All other company names, product names and logotypes are trademarks or registered trademarks of their respective owners. ©Sharp Corporation All trademarks acknowledged. E&O. Ref: Sharp/ NEC MultiSync EA271U, 14/7/2026