

Desktopdisplays

NEC MULTISYNC® EA242WU

NEC MultiSync

- Improve your Productivity – with embedded LAN and USB-C, this display serves as a docking hub in your Personal Workspace.
- Future-proof flexibility – wide connectivity provides high-level flexibility with LAN, DP, HDMI, USB Type C, USB A and audio output.
- Clutter-free workspace – Powerful 65W USB Type-C connectivity manages video, audio, power and USB via a single cable.
- Easy multi-screen set-up – Daisy-chain multiple display configurations through DisplayPort-out, no additional cables needed.
- Maximum attention to health and well-being – including ergonomic height adjustment; built-in Low Blue Light and Flicker-Free technology; plus integrated ambient light sensor.

Specificaties

Panel Technologie	IPS TFT with W-LED backlight
Aspect Ratio	16:10
Helderheid (cd/m ²)	300
Contrast Ratio	1000:1
[AVSpecificationDynamicContrastRatio]	5000:1
Kleuren Display	16.77
Reactietijd (grijs naar grijs gem) ms	6
Viewing Angle [°]	178
Special Characteristics	ControlSync®, CO2-besparingsmeter, DICOM-voorstelling, Aanpasbare instellingen, DDC/CI compatible, RGB Support, Frame Comp, ErgoDesign®, LED-achtergrondverlichtingstechnologie, Picture-by-Picture, PJLink-ondersteuning, Versatile and easy installation (VESA standard) with NaViSet and NaViKey, Aanraaktoetsen, USB versie 3.0 (3 omlaag / 1 omhoog), Niet-flikkerend
Optimum Resolution	1920 x 1200 at 60 Hz
Supported Resolution	1024 x 768 , 1280 x 1024, 1280 x 960, 1280 x 720, 1440 x 900, 1680 x 1050, 1920 x 1080, 640 x 480, 800 x 600, 1280 x 768, 1360 x 768, 1366 x 768, 1400 x 1050, 1600 x 1200, 1920 x 1200
Height adjustable stand [mm]	150
Screen Rotate [°]	-90 - 90
[AVSpecificationDimensionsWidthWithStandMm]	531
[AVSpecificationDimensionsHeightWithStandMm]	365
[AVSpecificationDimensionsDepthWithStandMm]	250
Bevestiging (VESA/Aantal Punten/Pitch mm)	100 x 100
Kensington-slot	True
Beelddiagonaal (inches / cm)	24
Beelddiagonaal (inches / cm)	61
Stroomverbruik aan-modus (IEC62087:2012)	12 (Eco Mode 2), 21 (typ.)
Power Supply	Internal Power Supply
Grootte Omlijsting (L/R) mm	1
Grootte Omlijsting (U) mm	1
Gewicht met standaard (kg)	7

Colour Versions	Zwarte voorkant, Zwarte achterkant, Witte voorkant, Witte achterkant
Cable Management	True
Plug & Play	VESA DDC2B, VESA DDCi
Audio	Koptelefoonaansluiting, Geïntegreerde speakers (1W + 1W)
Adjust Functions	Audiovolume / vergrendeling, Automatische aanpassing, Helderheid, Kleurtemperatuurregeling, Contrast, Control Sync, DV-modus, Eco-modus, Fijnafstelling (analoog), Aanwezigheidsensor, Intelligent stroombeheer, Taalkeuze, LED-helderheid, Monitorinformatie, NTAA (Non-Touch-Auto-Adjustment), OSD-vergrendeling (On-Screen-Display, beeldschermdisplay), One Touch Recovery, Uitschakeltimer, sRGB CE, EnergyStar 8.0, Flicker-free, Low Blue Light, TCO 9.0
Safety & Ergonomics	
Beperkte fabrieksgarantie (jaren.)	3 jaar garantie incl. achtergrondverlichting, Optionele verlenging van de garantie van 4 tot 5 jaar
Energy Efficiency	Ambient light sensor, Energy consumption: 13 kWh/1000 h, Energy efficiency class: D, Human sensor, Intelligent Power Management
Ecological Standards	Energy Star 8.0, TCO 9.0
Ecological Materials	Handleidingen zijn te downloaden
Digital	DisplayPort, DisplayPort out, HDMI, USB ver. 3.1 (2 down / 1 up), USB Type C (65 W)
Output Control	1 x RJ45
Accessoires	
Shipping Content	Monitor, Stroomkabel, Installatiegids, USB-C-kabel
Horizontal Frequency [kHz]	31.5 - 77
Vertical Frequency [Hz]	50 - 60
Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80
Werkende Temperatuur (oC)	5 - 35