

Desktopdisplays

Sharp/ NEC MultiSync® E244FL



For driving down costs without compromising quality, the E-series prioritises user comfort and productivity making it an excellent solution for both the home office and for small to medium sized businesses for general office applications.

- Improve your Productivity – with embedded LAN and USB-C, this display serves as a docking hub in your Personal Workspace.
- Future-proof flexibility – wide connectivity provides high-level flexibility with LAN, DP, HDMI, USB Type C, USB A and audio output.
- Safeguarding user wellbeing – built-in Low Blue Light technology filters out hazardous blue light emissions whilst Flicker-Free technology eliminates any backlight flickering.
- Ergonomic Office – full height adjustability (130 mm), swivel, tilt and pivot functionality ensures perfect individual workspace set-up.
- Best in form and function – future-ready design with 3-sided ultra-narrow bezel, available in black or white, plus optional VESA mount plate for thin client devices.

Specificaties

Panel Technologie	VA TFT with W-LED backlight
Aspect Ratio	16:9
Helderheid (cd/m ²)	250
Contrast Ratio	1000:1
Kleuren Display	16.77
Reactietijd (grijs naar grijs gem) ms	6
Pixel Pitch (mm H/V)	0,275
Viewing Angle [°]	178
Height adjustable stand [mm]	120
Screen Rotate [°]	-90 - 90
[AVSpecificationLandscapeDimensionsWidthMm]	610
[AVSpecificationLandscapeDimensionsDepthMm]	283
[AVSpecificationLandscapeDimensionsHeightMinMm]	377
[AVSpecificationLandscapeDimensionsHeightMaxMm]	507
Digital	DisplayPort, HDMI, USB Type C (60 W), USB ver. 3.1 (3 down / 1 up)
Output Control	1 x RJ45
Grootte Omlijsting (L/R) mm	1
Grootte Omlijsting (U) mm	16
Grootte Omlijsting (L) mm	16
Gewicht zonder standaard (kg)	5
Gewicht met standaard (kg)	8
Beelddiagonaal (inches / cm)	24
Beelddiagonaal (inches / cm)	60
Stroomverbruik aan-modus (IEC62087:2012)	13 (Eco Mode 2), 19 (typ.)
Power Supply	Integrated Power Supply
Special Characteristics	Low Blue Light, Local dimming

Colour Versions	Zwarte voorkant, Zwarte achterkant, Witte voorkant, Witte achterkant
Cable Management	True
Plug & Play	VESA DDC2Bi
Audio	1W + 1W (uitschakelbaar), Koptelefoonaansluiting
Safety & Ergonomics	EnergyStar 8.0, Flicker-free, Low Blue Light, RoHS, TCO 9.0, TÜV Ergonomics, TÜV GS, WEEE
Beperkte fabrieksgarantie (jaren.)	3 jaar garantie incl. achtergrondverlichting
Werkende Temperatuur (oC)	5 - 35
Storage Temperature [°C]	-10 - 60
Storage Humidity [%]	10
Storage Humidity [%]	85
Accessoires	
Shipping Content	DisplayPoort-kabel, Stroomkabel, Installatiegids, USB-C-kabel
Energy Efficiency	Carbon Footprint Meter / Carbon Savings Meter, ECOMode
Ecological Standards	Voldoet aan RoHS, TCO 9.0
Bevestiging (VESA/Aantal Punten/Pitch mm)	100 x 100
Kensington-slot	True
Horizontal Frequency [kHz]	31.5 - 81
Vertical Frequency [Hz]	50 - 75
Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80
Optimum Resolution	1920 x 1080 at 60 Hz

