

Desktopdisplays

NEC MULTISYNC EA272F



NEC MultiSync

- Veelgevraagd schermformaat - het populaire 27 inchscherm met Full HD-resolutie heeft het perfecte formaat voor drukke werkplekken op kantoor.
- Opgeruimde werkplek - De krachtige 65W USB-C-connectiviteit levert video, audio en USB via één kabel.
- Toekomstbestendige flexibiliteit - uitgebreide connectiviteit zorgt voor veel flexibiliteit met DP, HDMI, USB Type C, USB A en audio-uitgangen.
- Eenvoudige set-up voor meerdere schermen - Koppel meerdere schermconfiguraties door via de displaypoort-uitgang, er zijn geen extra kabels nodig.
- Maximale aandacht voor de gezondheid en het welzijn van de gebruiker - met uitstekende ergonomische hoogterverstelling tussen 0 en 150 mm; ingebouwde Low Blue Light- en Flicker-Free-technologie; plus g

Specificaties

Panel Technologie	AH-IPS LCD with LED backlight
Aspect Ratio	16:9
Helderheid (cd/m2)	250
Contrast Ratio	1000:1
[AVSpecificationDynamicContrastRatio]	5000:1
Kleuren Display	16.78
Reactietijd (grijs naar grijs gem) ms	6
Pixel Pitch (mm H/V)	0,311
Energy Efficiency	Ambient light sensor, Auto brightness, Carbon Footprint Meter / Carbon Savings Meter, ECOMode, Energy consumption: 15 kWh/1000 h, Energy efficiency class: D, Human sensor, LED backlight technology
Ecological Standards	Efficiënt mechanisch ontwerp, zodat er weinig verpakkingsmateriaal nodig is, Minimaal gebruik van schadelijk materiaal
Ecological Materials	Voldoet aan ErP, WEEE
Height adjustable stand [mm]	150
Screen Rotate [°]	-90 - 90
[AVSpecificationPortraitDimensionsWidthMm]	360
[AVSpecificationPortraitDimensionsDepthMm]	250
[AVSpecificationLandscapeDimensionsWidthMm]	610
[AVSpecificationLandscapeDimensionsDepthMm]	250
[AVSpecificationPortraitDimensionsHeightMinMm]	628
[AVSpecificationPortraitDimensionsHeightMaxMm]	652
[AVSpecificationLandscapeDimensionsHeightMinMm]	377
[AVSpecificationLandscapeDimensionsHeightMaxMm]	527
Optimum Resolution	1920 x 1080 at 60 Hz
Supported Resolution	1024 x 768 , 1280 x 1024, 1280 x 960, 1280 x 720, 1440 x 900, 1680 x 1050, 1920 x 1080, 640 x 480, 720 x 400 (70 Hz), 800 x 600
Werkende Temperatuur (oC)	5 - 35
Storage Temperature [°C]	-10 - 60
Storage Humidity [%]	10
Storage Humidity [%]	85
Digital	DisplayPort, DisplayPort out, HDMI, USB ver. 3.1 (3 down / 1 up), USB Type C
Analog	VGA
Grootte Omlijsting (L/R) mm	1
Grootte Omlijsting (U) mm	1
Grootte Omlijsting (L) mm	16
Horizontal Frequency [kHz]	31.5 - 83
Vertical Frequency [Hz]	55 - 75

Colour Versions	Zwarte voorkant, Zwarte achterkant, Witte voorkant, Witte achterkant
Cable Management	True
Plug & Play	DDC2B/2Bi, EDID Standard, VESA DDC/CI
Audio	Koptelefoonaansluiting, Geïntegreerde speakers (1W + 1W)
Adjust Functions	Audiovolume / vergrendeling, Automatische aanpassing, Helderheid, Kleurtemperatuurregeling, Contrast, Control Sync, DV-modus, Eco-modus, Factory Preset, Fijnafstelling (analoog), Aanwezigheidssensor, Intelligent stroombeheer, Taalkeuze, Monitorinformatie, NTAA (Non-Touch-Auto-Adjustment), OSD-vergrendeling (On-Screen-Display, beeldschermdisplay), One Touch Recovery, Uitschakeltimer, sRGB CE, EAC, EnergyStar 8.0, ErP, FCC Class B, Flicker-free, ISO 9241-307 (pixel failure class 2), ISO 9241-307 (pixel failure class I), Low Blue Light, PSB, RoHS, TCO 8.0, TÜV Ergonomics, TÜV GS, UL/C-UL or CSA, TCO Edge 2
Safety & Ergonomics	3 jaar garantie incl. achtergrondverlichting, Optionele verlenging van de garantie van 4 tot 5 jaar
Beperkte fabrieksgarantie (jaren.)	
Special Characteristics	DDC/CI compatible, RGB Support, Frame Comp, PLink-ondersteuning, Versatile and easy installation (VESA standard) with NaViSet and NaViKey, Aanraaktoetsen, USB versie 3.0 (3 omlaag / 1 omhoog)
Accessoires	
Shipping Content	Control Sync-kabel, DisplayPoort-kabel, Monitor, Stroomkabel, Installatiehandleiding, Installatiegids, USB-kabel, USB-C-kabel
Beelddiagonaal (inches / cm)	27
Beelddiagonaal (inches / cm)	69
Colour Gamuts	102 % sRGB, 75.5% AdobeRGB, 72% NTSC
Stroomverbruik aan-modus (IEC62087:2012)	15 (Eco Mode 2), 21 (typ.)
Power Supply	0.85 A/0.45 A, 100-240 V, Integrated Power Supply
Bevestiging (VESA/Aantal Punten/Pitch mm)	100 x 100
Kensington-slot	True

Operating Humidity (min) [%] 20
Operating Humidity (max) [%] 80

Gewicht met standaard (kg) 9



Design and specifications are subject to change without prior notice. All information was correct at time of print. Microsoft, Excel, PowerPoint, OneDrive, SharePoint, Active Directory, Windows Server, and Windows are either registered trademarks or trademarks of Microsoft Corporation in the US and/or other countries. Adobe and PostScript 3 are either registered trademarks or trademarks of Adobe Systems Incorporated in the US and/or other countries. Google Drive, Gmail, Android, and Google Cloud Print are trademarks of Google LLC. The Google Drive trademark is used with permission from Google LLC. Box is a trademark, service mark, or registered trademark of Box, Inc. QR Code is a registered trademark of DENSO WAVE INCORPORATED in Japan and other countries. AirPrint and Mac are trademarks of Apple Inc., registered in the US and other countries. PCL is a registered trademark of Hewlett_x0002_Packard Company. Qualcomm DirectOffice is a product of Qualcomm Technologies, Inc. and/or its subsidiaries. Qualcomm is a trademark of Qualcomm Incorporated, registered in the US and other countries. DirectOffice is a trademark of CSR Imaging US, LP, registered in the US and other countries. All other company names, product names and logotypes are trademarks or registered trademarks of their respective owners. ©Sharp Corporation All trademarks acknowledged. E&O. Ref: NEC MultiSync EA272F, 22/6/2026