

Digital Signage Display

MultiSync ME502



- Seamless connectivity – native USB-C supports Bring Your Own Device workflows, safeguarding inclusion and boosting productivity, with a single cable connection between notebook and display.
- Quick input detection – removing potential frustration and smoothing the way to productive meeting outcomes, the display responds immediately when a device is connected.
- New feature-ready – regular OTA Android OS updates ensure availability of the latest features and system security.
- Best readability – aiding high productivity in well-lit meeting spaces, a high haze filter eliminates glare and reflections from windows and other light sources.
- Third-party compatibility – not simply a display, but an out-of-the-box solution, compatible with popular workplace and content management systems through the integrated SoC platform.

Specificaties

DISPLAYMODULE GEGEVENS

Panel Technologie	VA with Direct LED backlights
Eigen resolutie (aantal pixels)	3840 x 2160
Beelddiagonaal (inches / cm)	50 / 125.7
Aspect Ratio	16:9
Backlight Technologie	LED
Helderheid (cd/m2)	450
Contrast Ratio	1200:1
Reactietijd (grijs naar grijs gem) ms	6
Kijkhoek (H/V)0 CR >10	178 horizontal / 178 vertical (typ. at contrast ratio 10:1)
Colour Depth [bn]	1.073 (8bit + FRC)
Haze Level [%]	Pro (25)

VOEDING EN BESTURINGSOMGEVING

Bedrijfsspanning (ACV) / Frequentie (Hz)	100-240 V AC; 50 / 60 Hz
Stroomverbruik (W) (MAX)	85 shipping
Werkende Temperatuur (oC)	0 to 40
Storage Temperature [°C]	-20 to 60
Vochtigheid (%)	20 to 80
Storage Humidity [%]	10 to 90

INSTALLATIE

Liggend	•
Staand	•
Bevestiging (VESA/Aantal Punten/Pitch mm)	400 x 400 (FDMI); 4 holes

CONNECTIVITEIT (AUDIO/VIDEO) OUTPUT

HDMI	1
Audio/Koptelefoon Aansluiting 3,5 mm	1

ACCESSOIRES

Shipping Content	2x AAA batteries; Display; HDMI Cable; Power Cable; Remote Control; Setup Manual
Zender Afstandsbediening	Yes
Netsnoer	Yes
Bevestigingsbeugel	Optional
Tafelstandaard	Optional
Batterij	Yes

BELANGRIJKSTE SPECIFICATIES

Special Characteristics	DICOM Simulation; HDMI ARC; Powered USB Port (15 W); Removable Logo
Beperkte fabrieksgarantie (jaren.)	3
Ingebouwde luidsprekers (W)	10 W + 10 W
Energiebeheer	•
Kleur Behuizing	Black

MATEN EN GEWICHTEN

Grootte Omlijsting (L/R) mm	9.9
Grootte Omlijsting (U/L) mm	9.9
Product Afmetingen (B/H/D) mm	1,118.6 x 639.2 x 62
Afmetingen Verpakkingsdoos (B/H/D) mm	1,202 x 719 x 156
Gewicht zonder standaard (kg)	11.7
Transportgewicht (Kg)	17.5

CONNECTIVITEIT (AUDIO/VIDEO) INPUT

HDMI	3
Audio-aansluiting van 3,5 mm	1

CONNECTIVITEIT (BEHEER /SERIËLE GEGEVENS

RS232C IN	1
LAN-poort	1
USB	4