

Sharp Signage Display

SHARP MULTISYNC® P506



Nauwkeurige prestaties voor kritische toepassingen.

- Verbeterde beeldprecisie – Sharp's SpectraView Engine biedt volledige controle over kleur, gamma en uniformiteit voor nauwkeurige en indrukwekkende content.
- Onbelemmerde leesbaarheid – een paneel met een hoge haze vermindert reflecties van ramen en omgevingslicht, waardoor de inhoud van de borden en presentaties helder en ongestoord leesbaar blijven in elke omgeving.
- Beveiliging gegarandeerd – 802.2x-ondersteuning via LAN zorgt voor een hoog beveiligingsniveau voor bedrijfsnetwerken, wat IT-teams en bedrijfsomgevingen gemoedsrust biedt.
- Cruciale prestaties – met een helderheid van 700 cd/m², duurzame componenten en een robuust, vlamvertragend metalen chassis is de P6-serie ontworpen om langdurige helderheid en duurzaamheid te leveren in veeleisende omgevingen, zonder dat er omvangrijke behuizingen nodig zijn.
- Betrouwbare integratie – volledige compatibiliteit met belangrijke AV-ecosystemen, waaronder Crestron XiO Cloud en NVX, Q-Sys, Cisco Webex, Matrox IPMX en CMS-oplossingen, garandeert een naadloze installatie en schaalbaarheid.

Specificaties

[AVSpecificationControlTerminals]	RS232C
Panel Technologie	VA with Direct LED backlights
Eigen resolutie (aantal pixels)	3840 x 2160
Aspect Ratio	16:9
Helderheid (cd/m2)	700
Contrast Ratio	8000:1
Pixel Pitch (mm H/V)	0,285
Viewing Angle [°]	178
Colour Depth [bn]	1073 (10bit)
Actief schermoppervlak (H / V) mm	1095 x 616
Response Time (typ.) [ms]	8
Bedrijfsspanning (ACV) / Frequentie (Hz)	100-240
Bedrijfsspanning (ACV) / Frequentie (Hz)	50-60
Via AC-Adapter	True
Werkende Temperatuur (oC)	0 - 40
Storage Temperature [°C]	-20 - 60
Storage Humidity [%]	10
Storage Humidity [%]	80
[AVSpecificationPowerSavingModeW]	< 2 (Networked Standby)
[AVSpecificationBattery]	< 0.5 (ECO Standby)
Staand	True
Liggend	True
Staand	True
Bevestiging (VESA/Aantal Punten/Pitch mm)	300 x 300 (FDMI)
Bevestiging (VESA/Aantal Punten/Pitch mm)	4
Bevestigingsbout Specificatie (grootte/Max Lengte)	M6
[AVSpecificationFaceUp]	True
[AVSpecificationFaceDown]	True
Afmetingen Verpakkingsdoos (B/H/D) mm	1245
Afmetingen Verpakkingsdoos (B/H/D) mm	785
Afmetingen Verpakkingsdoos (B/H/D) mm	188
Gewicht zonder standaard (kg)	18
Transportgewicht (Kg)	23
Energy Efficiency	Energy Consumption: 85kWh/1000 h, LED backlight technology, Energy efficiency class: G
Ecological Standards	Energy Star 8.0
Digital	DisplayPort, DisplayPort out, HDMI, USB Type C
Output Control	LAN 100Mbit
[AVSpecificationLandscapeDimensionsWidthMm]	1122
[AVSpecificationLandscapeDimensionsHeightMm]	645
[AVSpecificationLandscapeDimensionsDepthMm]	67
Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80

Colour Versions	Zwarte voorkant, Zwarte achterkant
Safety & Ergonomics	EMC Class B, UKCA, ISO 9241-307 (pixel failure class I), RoHS, UL/C-UL or CSA, FCC Class B, CE, EnergyStar 8.0, REACH
Beperkte fabrieksgarantie (jaren.)	3 jaar garantie incl. achtergrondverlichting, Optionele verlenging van de garantie van 4 tot 5 jaar, [additional-services-available]
Special Characteristics	CEC-ondersteuning, HDMI ARC, Planner, DICOM-simulatie, [clone-settings]
24/7 Werking Gecertificeerd	True
Ingebouwde luidsprekers (W)	10 + 10
Energiebeheer	True
Temperatuur Sensor	True
Beheer Afstandsbediening	True
Operating Time	24/7
Frame Material	Metal
Supported Resolution	1270 x 720, 1920 x 2160, 1920 x 1200, 1024 x 768, 1280 x 1024, 1600 x 1200, 1920 x 1080, 640 x 480, 800 x 600, 1280 x 720, 1440 x 900, 1680 x 1050, 3840 x 2160, 1360 x 768, 720 x 576, 720 x 400, 720 x 480, 1366 x 768, 1400 x 1050, 1280 x 800, 4096 x 2160
Accessoires	
[AVSpecificationAccessories]	[eco-sensor], [feet], [remote-control-kit], [soundbar], [speaker], [trolley], [usb-c-cable], [wall-mount]
Shipping Content	Installatiehandleiding, 2x AAA-batterijen, HDMI-kabel, Afstandsbediening, Weergave, Stroomkabel
Beelddiagonaal (inches / cm)	50
Beelddiagonaal (inches / cm)	126
Colour Gamuts	86% of DCI
Groote Omlijsting (L/R) mm	11
Groote Omlijsting (U) mm	11
Groote Omlijsting (L) mm	14
Horizontal Frequency [kHz]	15 - 135
Vertical Frequency [Hz]	23 - 76
Ingebouwde luidsprekers (W)	Internal 10W + 10W
Haze Level [%]	Pro 25



Design and specifications are subject to change without prior notice. All information was correct at time of print. Microsoft, Excel, PowerPoint, OneDrive, SharePoint, Active Directory, Windows Server, and Windows are either registered trademarks or trademarks of Microsoft Corporation in the US and/or other countries. Adobe and PostScript 3 are either registered trademarks or trademarks of Adobe Systems Incorporated in the US and/or other countries. Google Drive, Gmail, Android, and Google Cloud Print are trademarks of Google LLC. The Google Drive trademark is used with permission from Google LLC. Box is a trademark, service mark, or registered trademark of Box, Inc. QR Code is a registered trademark of DENSO WAVE INCORPORATED in Japan and other countries. AirPrint and Mac are trademarks of Apple Inc., registered in the US and other countries. PCL is a registered trademark of Hewlett_x0002_Packard Company. Qualcomm DirectOffice is a product of Qualcomm Technologies, Inc. and/or its subsidiaries. Qualcomm is a trademark of Qualcomm Incorporated, registered in the US and other countries. DirectOffice is a trademark of CSR Imaging US, LP, registered in the US and other countries. All other company names, product names and logotypes are trademarks or registered trademarks of their respective owners. ©Sharp Corporation All trademarks acknowledged. E&O. Ref: Sharp MultiSync® F506, 23/6/2026