

NEC U310W

ORDER CODE: 60003137

NEC U310W Professional Ultra-Short-Throw Solution

Enjoy large images even in meeting rooms with small space. Less shadow and glare gives the presenter more space to engage with his audience and enhances the experience with interactive white boards. Go wide with your presentations and play video content in native aspect ratio. Free installation angles give you additional freedom for eye catching digital signage installations. DLP technology ensures that there is no color decay during long daily operating hours. 3D capability makes you ready for next generation digital content.

An ideal solution for meeting rooms and digital signage applications, as well as for classrooms.



DELIVERING GENUINE BENEFITS

Almost no shadow and glare - thanks to ultra-short throwing distance.

Wall-mount included - for quick and easy installation, compatible with height adjustable systems.

3D ready - future-proof DLP®-Link™ technology with 120Hz.

Free tilting - for desktop use as well as ceiling and floor projection.

Great connectivity - due to numerous analog and digital connection terminals as well as network capability.

Wide format - for extra space in presentations and video content in native aspect ratio - no quality loss due to format scaling.

OUTSTANDING PERFORMANCE

- **High Brightness** - 3100 ANSI lumens
- **Ultra-Short Throw Ratio** - 0.3:1
- **Long Lamp Life** - up to 3000 hrs
- **Virtual Remote** for full control via VGA
- **Speaker** with 10W
- **Long Life Filter** for longer cleaning intervals



SPECIAL CHARACTERISTICS

3D-valmis; 6-segment Colour Wheel; Auto Power ON/OFF; BrilliantColor™ and VIDI technology; Kensington-turvalukko; Long Life Lamp; Manual vertical Keystone Correction ($V = \pm 15^\circ$); Manual Wall Color Correction; Off-Timer; Plug&Play; Quick-Start-/Quick-Power-Off Function; Security Bar; vapaasti kääntyvä



ECO Innovation: Green one touch ECO and AV mute button

Energy Efficiency: Intelligent Power Management; Reduced power consumption. Only 0,5W stand-by; Software scheduling

Ecological Materials: 100% recyclable packaging; Downloadable manuals

Ecological Standards: RoHS compliant; WEEE; ErP compliant

Technical Specification NEC U310W

IMAGE	
Display	1 x 1,65 cm (0,65") 2 x LVDS DMD (kuvasuhde 16:10)
Native Resolution	1280 x 800 (WXGA)
Brightness ¹	3100 ANSI Lumens
Contrast Ratio ¹	2000:1
Lamp	280 W AC
Lamp Life [hrs]	2500 (3000 Eco Mode)
Lens	F= 2,71, f= 4,42 mm
Projection Factor	0,3 : 1
Projection Angle [°]	55,3
Projection Distance [m]	0,152 – 0,319
Screen Size (diagonal) [cm]	Minimum: 196 / 77"; Maximum: 254 / 100"
Zoom	Manual; Digital Zoom
Supported Resolutions	VGA; SVGA; XGA; WXGA; SXGA; SXGA+; UXGA
Frequency	Horizontal: 15–91,1 kHz (RGB: 31,35 kHz– 91,1 kHz); Vertikaalisesti: 50 – 85 Hz (120 Hz: vain 3D-signaalille)
CONNECTIVITY	
RGB (analog)	Input: 2 x Mini D-sub 15-pin, compatible to component (YPbPr); Output: 1 x Mini D-sub 15 pin
Video	Input: 1 x RCA
HDMI®	Input: 1 x HDMI® (Deep Color, Lip sync) with HDCP
S-Video	Input: 1 x Mini DIN 4-pin
Audio	Input: 2 x 3.5 mm Stereo Mini Jack; Input: 1 x RCA Stereo for Video and S-Video; Output: 1 x 3.5 mm Stereo Mini Jack
PC Control	Input: 1 x D-Sub 9 pin (RS-232) (male)
LAN	1 x RJ45
Video Signals	PAL; PAL60; NTSC; SECAM; NTSC 4.43; PAL-N; PAL-M
REMOTE CONTROL	
Remote Control	Source Select; Keystone Correction; Auto Adjust; Aspect Ratio; Mute-function; Volume; Picture Adjust; Audio Control; Picture Mode; Eco-painike; Jäädytys; Apu-Eco-mode; Digitaalinen zoom; Esitys- ja hiiriohjaus; AV-mykistys; ID-asetus
ELECTRICAL	
Power Supply	100-240 V AC; 50 - 60 Hz
Power Consumption [W]	360 (Normal) / 315 (Eco) / 0,5 (Network Stand-by) / 0,5 (Stand-by)
MECHANICAL	
Dimensions (W x H x D) [mm]	427 x 200 x 406 (without lens and feet)
Weight [kg]	6,5
Fan Noise [dB (A)]	32 / 36 (Eco / Normal)
ENVIRONMENTAL CONDITIONS	
Operating Temperature [°C]	5 to 35
Operating Humidity [%]	20 to 80
Storage Temperature [°C]	-10 to 50
Storage Humidity [%]	20 to 80
OPTIONAL ACCESSORIES	
Optional Accessories	Lamp (NP20LP); Motorized Height Adjustable Wall Mount NP01HW; Mobile Motorized Wall Mount NP01HM; Manual Height Adjustable Wall Mount NP01HWM
ERGONOMICS	
Safety and Ergonomics	CE; TÜV GS; ErP; RoHS
Speakers [W]	1 x 10 (mono)
WARRANTY	
Projectors	3 years pan-European service
Lamp	6 months, max. 1000 hrs
SHIPPING CONTENT	
Shipping Contents	Projector; IR Remote Control with Batteries; Power Cord (3,0 m); VGA-kaapeli (3,0 m); Seinäasennussarja NP01WK; Users Manual on CD-ROM; Quick Setup Guide

¹Compliance with ISO21118-2005